



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 08 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

A.MIG-2013

A-Stand Airbrush Cleaner

UFI: YCU0-Q0KC-W005-452S

1.2 Relevant identified uses of the substance or mixture and uses advised against

Paint for scale models and modelling.

1.3 Details of the supplier of the safety data sheet

Supplier

Mig Jimenez, S.L.
C/Zarapuz 3. 31200 Estella, Navarra (España)
Telephone: +34 948 552 882
Email: order@ammo.es
Website: www.migjimenez.com

Manufacturer

H&R Hobbies Ltd
Unit 2B, The Follys, Gaymers North Walsham
NR28 0AN Norfolk (United Kingdom)
Telephone: +44 1692 500 700
Email: technical@hrhobbies.com

1.4 Emergency Telephone Number

Telephone: +34 917689800 Instituto Nacional de Toxicología y Ciencias Forenses (INTCF)

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to Regulation (EC) No. 1272/2008 (CLP):

Flam. Liq. 2 – Highly flammable liquid and vapour. H225

Eye Irrit. 2 – Causes serious eye irritation. H319

STOT SE 3 – May cause drowsiness or dizziness. H336

EUH066 – Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

According to Regulation (EU) No. 1272/2008:

Pictograms:



GHS02



GHS07

Signal word: **DANGER**

Contains: Acetone, 2-methoxy-1-methylethyl acetate.



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 08 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

Hazard statements:

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use recommended extinguishing media.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

2.3 Other hazards

PBT/vPvB assessment:

According to Annex XIII of Regulation (EC) No. 1907/2006 (REACH), this product does not meet the criteria for classification as PBT (Persistent, Bioaccumulative and Toxic) or vPvB (very Persistent and very Bioaccumulative).

Physicochemical hazards

Possible electrostatic charge buildup with risk of ignition. Vapours may form potentially flammable or explosive mixtures with air.

3 COMPOSICIÓN/INFORMACIÓN SOBRE LOS COMPONENTES

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 08 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

3.2 Mixtures

Chemical nature:

80%-100% ACETONE

CAS Number: 67-64-1

EINECS Number: 200-662-2

Classification Number: 606-001-00-8

Registration Number: 01-2119471330-49-XXXX

Flam. Liq. 2: Highly flammable liquid and vapour. H225

Eye Irrit. 2: Causes serious eye irritation. H319

STOT SE 3: May cause drowsiness or dizziness. H336

EUH066 Repeated exposure may cause skin dryness or cracking

4 FIRST AID MEASURES

4.1 Description of first aid measures

GENERAL INFORMATION: Symptoms may occur after exposure. Therefore, in cases of direct exposure to the product, whenever in doubt or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. First aid responders should pay attention to their own protection and use the recommended personal protective equipment if exposure is possible. Wear protective gloves when administering first aid.

INGESTION: Do not induce vomiting. Do not give anything by mouth. If vomiting occurs spontaneously, keep the head below hip level to prevent aspiration. Seek medical attention.

INHALATION: Remove the affected person to fresh air and keep at rest. If breathing is irregular or stops, administer artificial respiration. If unconscious, place in the recovery position. If recovery is not rapid, transport the person to the nearest medical facility for further treatment.

EYE CONTACT: Immediately rinse eyes with plenty of water for at least 15 minutes while keeping eyelids open. Seek medical attention. Prevent the affected person from rubbing or closing the eyes. If the injured person wears contact lenses, remove them whenever possible unless they are adhered to the eye, as additional damage may occur.

SKIN CONTACT: Remove contaminated clothing immediately. Wash the affected area thoroughly with soap and plenty of water. Seek medical advice. If the product causes burns or frostbite, do not remove clothing if it is adhered to the skin, as this may worsen the injury. If blisters form, do not break them as this increases the risk of infection.

4.2 Most important symptoms and effects, both acute and delayed

INGESTION: Harmful if swallowed. May cause abdominal pain and weakness.

INHALATION: Slightly irritating to the respiratory system. Inhalation of vapours may cause drowsiness and dizziness. Symptoms of respiratory irritation may include a temporary burning sensation of the nose and throat, coughing and/or breathing difficulties. If the product enters the lungs, coughing, choking, wheezing, breathing difficulties, chest congestion, shortness of breath and/or fever may occur. Breathing high concentrations of vapour may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

EYE CONTACT: Irritating to the eyes. Symptoms may include burning sensation, redness, swelling and/or blurred vision.

SKIN CONTACT: May cause moderate skin irritation. Repeated exposure may cause dermatitis, skin dryness or cracking.



SAFETY DATA SHEET In accordance with Regulation (EC) No 1907/2006		
A-STAND 08 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed, the product may be aspirated into the lungs and cause chemical pneumonitis. Seek advice from a physician or poison centre. No specific antidote is known.

5 FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Preferably use multipurpose dry powder extinguishers (ABC powder). Alcohol-resistant foam, water spray, dry chemical powder or carbon dioxide may also be used. Sand or earth may only be used for small fires.

Unsuitable extinguishing media: Do not use direct water jets, as they may be ineffective or may spread the product.

5.2 Special hazards arising from the substance or mixture

Highly flammable. Combustion or thermal decomposition may generate hazardous decomposition products which may present a significant health risk. Incomplete combustion may produce carbon monoxide. Vapours are flammable and heavier than air. Vapours may travel along the ground and reach distant ignition sources, causing flashback fire hazards. Liquid residues entering drains may create a fire or explosion hazard.

Hazardous decomposition products: Carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Wear a complete heat-resistant protective suit, self-contained breathing apparatus in the presence of dense smoke, protective gloves, safety goggles or face shield and protective boots. Emergency equipment should be available (fire blankets, portable first-aid kit, etc.). Eliminate all sources of sparks and ignition. No smoking. Cool containers/tanks with water spray. Take wind direction into account. Prevent fire-fighting water and extinguishing media from entering drains, sewers or watercourses.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Isolate the spill area provided that doing so does not pose an additional risk to personnel carrying out this task and prevent access by unnecessary personnel. Evacuate the area and keep unprotected persons away. Avoid the formation of flammable vapour-air mixtures, either by ventilation or by the use of an inerting agent. Avoid contact with skin and eyes and inhalation of vapours. Remove all contaminated clothing and use appropriate personal protective equipment. Do not smoke. Take precautionary measures against electrostatic discharges.

6.2 Environmental precautions

Avoid contamination of drains, surface water, groundwater and soil.

6.3 Methods and material for containment and cleaning up

Comply with all applicable local and international regulations.

Absorb the spill with non-combustible absorbent materials (earth, sand, vermiculite, diatomaceous earth, etc.). Place the product and absorbent material into a suitable container.

The contaminated area should be cleaned immediately using an appropriate decontaminating agent. Apply the decontaminating agent to the residues and leave it for several days until no further reaction occurs, in an unsealed container.

6.4 Reference to other sections

For exposure controls and personal protection measures, see Section 8.

For waste disposal recommendations, see Section 13.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 08 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

7 HANDLING AND STORAGE

7.1 Precautions for safe handling

Vapours are heavier than air and may spread along the ground. They may form explosive mixtures with air. Avoid the formation of flammable or explosive vapour concentrations in air and avoid vapour concentrations exceeding occupational exposure limits.

The product should only be used in areas where all naked flames and other ignition sources have been eliminated. Electrical equipment must be protected in accordance with the appropriate standards.

The product may become electrostatically charged; always use grounding connections when transferring the product. Operators should wear antistatic footwear and clothing, and floors should be conductive.

Keep the container tightly closed and away from heat, sparks and flames. Do not use tools that may produce sparks.

Avoid contact with skin and eyes. Avoid inhalation of vapours and mists generated during spraying. For personal protection, see Section 8. Never use pressure to empty containers; they are not pressure-resistant vessels.

Smoking, eating and drinking should be prohibited in the application area.

Comply with occupational safety and hygiene legislation.

Keep the product in containers made of the same material as the original container.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Follow the instructions on the label. Store containers between 5°C and 35°C in a dry, well-ventilated place away from heat sources and direct sunlight. Keep away from ignition sources. Keep away from oxidising agents and strongly acidic or alkaline materials. Do not smoke. Prevent access by unauthorised persons. Once opened, containers must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)

No data available.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure limit:

	Environmental Exposure Limit Value (Daily Exposure)		Environmental Exposure Limit Value (Short-Term Exposure)	
	ppm	mg/m ³	ppm	mg/m ³
ACETONE	500	1210	1500	3620

	DNEL WORKERS – END USE Chronic systemic effects		DNEL WORKERS – END USE Chronic systemic effects		
	Dermal	Inhalation	Dermal	Inhalation Long-term local effects	Inhalation Short-term local effects
ACETONE	62 mg/Kg/day	200 mg/m ³	186 mg/Kg/day	1210 mg/m ³	2420 mg/m ³

8.2 Exposure controls

Engineering measures

Provide adequate ventilation, which can be achieved by means of effective local exhaust ventilation and a suitable general extraction system.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 08 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

Respiratory protection

Where high concentrations occur (see OEL), use self-contained breathing apparatus fitted with an organic vapour filter. CE marking, Category III. The mask shall provide a wide field of vision and an anatomical fit to ensure a proper seal.

Hand protection

Protective rubber gloves.

Eye protection

Full eye protection goggles.

Skin protection

Where splashing is anticipated, use full protective equipment.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state: Liquid

Colour: No data available

Odour: No data available

Melting point: -95°C

Boiling point/range: 56°C (Acetone)

Flammability: No data available

Upper and lower explosive limits: Lower: 2.1% (vol) – Upper: 11.5% (vol)

Flash point: -17°C (Acetone)

Auto-ignition temperature: 465°C

Decomposition temperature: No data available

pH (1% H₂O): No data available

Kinematic viscosity: No data available

Water solubility: Completely soluble

n-octanol/water partition coefficient (log Pow): No data available

Vapour pressure (20°C): No data available

Relative density: No data available

Relative vapour density: No data available

Particle characteristics: The molecule does not contain chemical groups associated with explosive properties.

9.2 Other information

No data available.

10 STABILITY AND REACTIVITY

10.1 Reactivity

No hazardous reactions are expected if the technical storage instructions are followed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions are known under normal conditions of use.

10.4 Conditions to avoid

Avoid heat, sparks, flames and other sources of ignition. Avoid extreme humidity conditions and exposure to direct sunlight.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

None under normal storage conditions.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 08 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

11 TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Toxicological data: Dermal: LD50 > 7400 mg/Kg rabbit
Oral: LD50 > 5800 mg/Kg rat

Skin corrosion/irritation: Not classified as a skin irritant.

Serious eye damage/eye irritation: Category 2: H319 – Causes serious eye irritation.

Respiratory sensitisation: Not classified.

Skin sensitisation: Not classified.

Mutagenicity: Not expected.

Carcinogenicity: Not expected.

Reproductive toxicity: Not classified.

Effects on or via lactation: Not classified.

Specific target organ toxicity (STOT) – single exposure:

STOT SE Category 3: H336 – May cause drowsiness or dizziness by inhalation (narcotic effects). Central nervous system: may cause headaches, dizziness, nausea, vomiting, confusion and, in severe cases, loss of consciousness.

Specific target organ toxicity (STOT) – repeated exposure:

Low systemic toxicity under repeated exposure conditions. Repeated exposure may cause skin dryness and cracking. No organ damage is expected from prolonged or repeated exposure.

11.2 Information on other hazards

Endocrine disrupting properties: Does not have endocrine disrupting potential.

Other hazards: None known.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Name			Ecotoxicity
Type	Test	Species	Value
Fish	LC50	Pimephales promelas	6210 – 8120 mg/l Source: ECHA
Aquatic invertebrates	EC50	Daphnia magna	> 79 mg/l

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

Significant bioaccumulation is not expected: (Log Pow = -0.24).



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 08 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product:

Recover or recycle where possible.

Contaminated packaging:

Disposal must be carried out in accordance with applicable regional, national and local laws and regulations.

14 TRANSPORT INFORMATION

14.1 UN number or ID number UN1090

14.2 UN proper shipping name ACETONE

14.3 Transport hazard class(es) 3
LABEL 3

14.4 Packing group II

14.5 Environmental hazards NO

14.6 Special precautions for user

Ensure that people transporting the product know what to do in the event of an accident or spillage. Always transport in tightly closed containers, kept upright and secure. Ensure adequate ventilation.

Tunnel restriction code: D/E

Hazard identification number: 33

LIMITED QUANTITIES:

1 L inner packaging

EXCEPTED QUANTITIES:

E2 – 30 ml/g per inner packaging and 500 ml/g per outer packaging (max. 1000 packages per transport unit)

14.7 Maritime transport in bulk according to IMO instruments

Not relevant.

15 REGULATORY INFORMATION



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 08 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet has been prepared in accordance with Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

This product is not subject to Regulation (EC) No. 1005/2009 of the European Parliament and of the Council on substances that deplete the ozone layer.

Regulation (EU) No. 649/2012 concerning the export and import of hazardous chemicals: not relevant.

Active substances included in Article 95 of Regulation (EU) No. 528/2012: not relevant.

SEVESO III

P5c – FLAMMABLE LIQUIDS

Threshold quantity (tonnes) for the application of requirements: 5,000 – 50,000 tonnes.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not yet been carried out due to registration deadlines.

16 OTHER INFORMATION

This product must be stored, handled and used in accordance with good industrial hygiene practices.

This information reflects our current knowledge. It describes the product and should not be construed as a product specification.

The application of this information does not exempt the user from complying with current legislation.

The use of this information and the conditions of use of the product are the sole responsibility of the user.

Sources of information: Safety Data Sheets provided by our suppliers, to whose expertise and information we refer.