



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

A.MIG-2300	A-STAND Aluminium
A.MIG-2301	A-STAND Duraluminium
A.MIG-2302	A-STAND Dark Aluminium
A.MIG-2303	A-STAND Pale Burnt Metal
A.MIG-2305	A-STAND White Aluminium
A.MIG-2307	A-STAND Pale Gold
A.MIG-2308	A-STAND Polished Brass
A.MIG-2309	A-STAND Copper
A.MIG-2310	A-STAND Magnesium
A.MIG-2311	A-STAND Steel
A.MIG-2312	A-STAND Jet Exhaust
A.MIG-2315	A-STAND Semi Matt Aluminium
A.MIG-2316	A-STAND Dull Aluminium
A.MIG-2319	A-STAND Gunmetal
A.MIG-2320	A-STAND Burnt Iron
A.MIG-2321	A-STAND Engine Manifold
A.MIG-2400	A-STAND Transparent Medium
A.MIG-2401	A-STAND Transparent Red
A.MIG-2402	A-STAND Transparent Yellow
A.MIG-2403	A-STAND Transparent Blue
A.MIG-2404	A-STAND Transparent Green
A.MIG-2405	A-STAND Transparent Smoke

UFI: FN80-F0DK-T006-VU1G

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Paint for scale models and modelling.

1.3 Details of the Supplier of the Safety Data Sheet

Supplier

Mig Jimenez, S.L.
C/Zarapuz 3. 31200 Estella, Navarra (España)
Telephone: +34 948 552 882
Email: order@ammo.es
Website: www.migjimenez.com

Manufacturer

H&R Hobbies Ltd
Unit 2B, The Follys, Gaymers North Walsham
NR28 0AN Norfolk (United Kingdom)
Telephone: +44 1692 500 700
Email: technical@hrhobbies.com

1.4 Emergency Telephone Number

Telephone: +34 917689800 Instituto Nacional de Toxicología y Ciencias Forenses (INTCF)



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 01 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

2 HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Según el Reglamento (CE) N° 1272/2008 (CLP):

According to Regulation (EC) No. 1272/2008 (CLP):

Flam. Liq. 2, H225 Highly flammable liquid and vapour.

Asp. Tox. 1, H304 May be fatal if swallowed and enters airways.

Acute Tox. 4, H312 Harmful in contact with skin.

Skin Irrit. 2, H315 Causes skin irritation.

Eye Irrit. 2, H319 Causes serious eye irritation.

STOT SE 3, H335 May cause respiratory irritation.

STOT SE 3, H336 May cause drowsiness or dizziness.

STOT RE 2, H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

2.2 Label Elements

According to Regulation (EC) No. 1272/2008:

Pictograms:



GHS02

GHS07

Signal word: **DANGER**

Contains: Acetone, n-Butyl acetate, Methyl ethyl ketone, Xylene and Aromatic hydrocarbons C9

Hazard Statements:

Flam. Liq. 2, H225 Highly flammable liquid and vapour.

Asp. Tox. 1, H304 May be fatal if swallowed and enters airways.

Acute Tox. 4, H312 Harmful in contact with skin.

Skin Irrit. 2, H315 Causes skin irritation.

Eye Irrit. 2, H319 Causes serious eye irritation.

STOT SE 3, H335 May cause respiratory irritation.

STOT SE 3, H336 May cause drowsiness or dizziness.

STOT RE 2, H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools only.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use recommended extinguishing media to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

2.3 Other Hazards

PBT/vPvB Assessment

According to Annex XIII of Regulation (EC) No. 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): this mixture does not meet the criteria for classification as PBT (persistent, bioaccumulative and toxic) or vPvB (very persistent and very bioaccumulative).

Physicochemical Hazards

Electrostatic charges may accumulate and create ignition hazards.

Vapours may form potentially flammable or explosive mixtures with air.

3 COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

	%	PELIGROS		
ACETONE CAS: 67-64-1 EINECS: 200-662-2 Reg.No.: 01-2119471330-49	50-70%	Flam. Liq. 2 H225 Eye Irrit. 2 H319 STOT SE 3 H336 EUH066		
n-Butyl acetate CAS: 123-86-4 EINECS: 204-658-1 Reg.No.: 01-2119485493-29	15-25%	Flam. Liq. 3, H226 STOT SE 3, H336, EUH066		
Methyl ethyl ketone CAS: 78-93-3 EINECS: 201-159-0 Reg.No.: 01-2119457290-43	10-20%	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066		
Xylene	4-5%	Flam. Liq. 3, H226		



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

CAS: 1330-20-7 EINECS: 215-535-7 Reg.No.: 01-2119488216-32		STOT RE 2, H373; Asp. Tox.1, H304; Acute Tox. 4, H312 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335		
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC No.: 918-668-5 Reg.No.: 01-2119455851-35	<1%	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336, EUH066		

4 FIRST AID MEASURES

4.1 Description of First Aid Measures

GENERAL INFORMATION: Symptoms may appear after exposure. Therefore, in the event of direct exposure to the product, if there is any doubt or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. Rescuers should pay attention to their own protection and use the recommended personal protective equipment if there is a possibility of exposure. Wear protective gloves when administering first aid.

INGESTION: Do not induce vomiting. Do not give anything by mouth. If vomiting occurs spontaneously, keep the head below hip level to prevent aspiration. Seek medical attention.

INHALATION: Remove the affected person to fresh air and keep at rest. If breathing is irregular or stops, administer artificial respiration. If unconscious, place the person in the recovery position. If recovery is not rapid, transport the affected person to the nearest medical facility for further treatment.

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes, keeping the eyelids open. Seek medical attention. Prevent the affected person from rubbing or closing the eyes. Contact lenses should be removed if present and easy to do, provided they are not adhered to the eye.

SKIN CONTACT: Remove contaminated clothing immediately. Wash the affected area thoroughly with soap and plenty of water. Seek medical attention. If the product causes burns or frostbite, do not remove clothing that is stuck to the skin, as this may worsen the injury. If blisters develop, do not puncture them, as this increases the risk of infection.

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

INGESTION: Harmful if swallowed. May cause abdominal pain and weakness.

INHALATION: Slightly irritates the respiratory system. Inhalation of vapours may cause drowsiness and dizziness. Symptoms of respiratory irritation may include a temporary burning sensation of the nose and throat, coughing and/or breathing difficulties. If the product enters the lungs, it may cause coughing, choking, wheezing, breathing difficulties, chest congestion, shortness of breath and/or fever. Exposure to high vapour concentrations may cause central nervous system (CNS) depression, resulting in dizziness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

EYE CONTACT: Causes eye irritation. Symptoms may include burning sensation, redness, swelling and/or blurred vision.

SKIN CONTACT: May cause moderate skin irritation. Repeated exposure may cause dermatitis, skin dryness or cracking.



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 01 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed

If swallowed, the product may be aspirated into the lungs and cause chemical pneumonitis. Seek advice from a physician or Poison Centre. No specific antidote is known.

5 FIREFIGHTING MEASURES

5.1 Extinguishing Media

Suitable extinguishing media:

Preferably use multipurpose dry chemical extinguishers (ABC powder). Alcohol-resistant foam, water spray, dry chemical powder or carbon dioxide may also be used. For small fires only, sand or earth may be used.

Unsuitable extinguishing media:

Do not use direct water jet, as it may be ineffective or may spread the product.

5.2 Special Hazards Arising from the Substance or Mixture

Highly flammable. Combustion or thermal decomposition may generate hazardous decomposition products that may be highly toxic and therefore present a significant health hazard. Incomplete combustion may produce carbon monoxide. Vapours are flammable and heavier than air. Vapours may travel along the ground and reach remote ignition sources, causing flashback fire hazards. Liquid residues entering drains or sewers may create a fire or explosion hazard.

Hazardous combustion products: Carbon monoxide and carbon dioxide.

5.3 Advice for Firefighters

Wear full heat-resistant protective clothing, self-contained breathing apparatus in the presence of dense smoke, protective gloves, safety goggles or face shield, and protective boots. Emergency facilities and firefighting equipment should be available (fire blankets, portable first-aid kit, etc.). Eliminate all sources of sparks and ignition. No smoking. Cool containers and tanks with water spray. Take wind direction into account. Prevent firefighting water and extinguishing residues from entering drains, sewers or watercourses.

6 ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Isolate the spill area whenever this does not create additional risk for personnel carrying out these tasks and prevent the entry of unnecessary personnel. Evacuate the area and keep unprotected persons away. Prevent the formation of flammable vapour-air mixtures, either by adequate ventilation or by the use of an inerting agent. Avoid contact with skin and eyes and avoid inhalation of vapours. Remove all contaminated clothing and wear suitable personal protective equipment. No smoking. Take precautionary measures against electrostatic discharges.

6.2 Environmental Precautions

Avoid contamination of drains, surface waters, groundwater and soil.

6.3 Methods and Material for Containment and Cleaning Up

Comply with all applicable local and international regulations.

Absorb the spill with non-combustible absorbent materials (soil, sand, vermiculite, diatomaceous earth, etc.). Transfer the collected material and absorbent into a suitable container. The contaminated area must be cleaned immediately using an appropriate decontaminating agent. Apply the decontaminating agent to the residues and leave it to act for several days in an unsealed container until no further reaction occurs.

6.4 Reference to Other Sections

For exposure controls and personal protective measures, see Section 8.

For disposal considerations, follow the recommendations given in Section 13.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

7 HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Vapours are heavier than air and may spread along the ground. They may form explosive mixtures with air. Avoid the formation of flammable or explosive vapour concentrations in air and avoid vapour concentrations exceeding occupational exposure limits. The product should only be used in areas where all unprotected flames and other ignition sources have been eliminated. Electrical equipment shall be protected in accordance with the applicable regulations.

The product may become electrostatically charged; always use proper grounding procedures when transferring the product. Operators should wear antistatic footwear and clothing, and floors should be electrically conductive.

Keep containers tightly closed and away from heat, sparks and open flames. Do not use tools that may generate sparks.

Avoid contact with skin and eyes. Avoid inhalation of vapours and mists generated during spraying operations. For personal protection, refer to Section 8. Never use pressure to empty containers; they are not pressure-resistant vessels.

Smoking, eating and drinking must be prohibited in the application area.

Comply with occupational health and safety regulations.

Keep the product only in containers made of the same material as the original packaging.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Store in accordance with local regulations. Follow the precautions stated on the label. Store containers between 5 °C and 35 °C in a dry, well-ventilated place away from heat sources and direct sunlight. Keep away from ignition sources. Keep away from oxidizing agents and strongly acidic or alkaline materials. No smoking. Prevent access by unauthorized persons. Once opened, containers must be carefully resealed and kept upright to prevent leakage.

7.3 Specific End Use(s)

No data available.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

Exposure Limits:

	Occupational Exposure Limit Long-term Exposure		Occupational Exposure Limit Short-term Exposure	
	ppm	mg/m3	ppm	mg/m3
ACETONE	500	1210	1500	3620

	DNEL WORKERS FINAL USE Chronic Systemic Effects		DNEL WORKERS FINAL USE Chronic Systemic Effects		
	Dermal	Inhalación	Dermal	Inhalación Long-term local effects	Inhalación Short-term local effects
ACETONA	62 mg/kg/day	200 mg/m3	186 mg/kg/day	1210 mg/m3	2420 mg/m3

8.2 Exposure Controls

Technical measures

Provide adequate ventilation, which can be achieved through effective local exhaust ventilation and a suitable general extraction system.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

Respiratory protection

In case of high concentrations (see OEL), use respiratory protection equipment fitted with a filter for organic vapours. CE Marking, Category III. The mask should provide a wide field of vision and an anatomical fit to ensure a proper seal.

Hand protection

Protective rubber gloves.

Eye protection

Full-seal safety goggles.

Skin protection

Where splashing is anticipated, wear full protective clothing.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties

Property	Value
Physical state	Liquid
Colour	No data available
Odour	No data available
Melting point	-95 °C
Boiling point/range	56 °C (Acetone)
Flammability	No data available
Upper and lower explosion limits	Lower: 2.1 % (vol) – Upper: 11.5 % (vol)
Flash point	-17 °C (Acetone)
Auto-ignition temperature	465 °C
Decomposition temperature	No data available
pH (1 % H ₂ O)	No data available
Kinematic viscosity	No data available
Water solubility	Completely soluble
Partition coefficient n-octanol/water (log Pow)	No data available
Vapour pressure (20 °C)	No data available
Relative density	No data available
Relative vapour density	No data available
Particle characteristics	The molecule contains no chemical groups associated with explosive properties

9.2 Other Information

No data available.

10 STABILITY AND REACTIVITY

10.1 Reactivity

No hazardous reactions are expected if the technical storage instructions are observed.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of Hazardous Reactions

No hazardous reactions are known under normal conditions of use.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

10.4 Conditions to Avoid

Avoid heat, sparks, flames and other ignition sources. Avoid extreme humidity conditions and exposure to direct sunlight.

10.5 Incompatible Materials

No data available.

10.6 Hazardous Decomposition Products

None under normal storage conditions.

11 TOXICOLOGICAL INFORMATION

11.1 Information on Hazard Classes as Defined in Regulation (EC) No. 1272/2008

Toxicological Data:

Route	Value
Dermal	LD50 > 7400 mg/kg (rabbit)
Oral	LD50 > 5800 mg/kg (rat)

Skin Corrosion/Irritation:	Not classified as a skin irritant.
Serious Eye Damage/Eye Irritation:	Category 2: H319 – Causes serious eye irritation
Respiratory Sensitisation:	Not classified
Skin Sensitisation:	Not classified
Germ Cell Mutagenicity:	Not expected
Carcinogenicity:	Not expected
Reproductive Toxicity:	Not classified
Effects on or via Lactation:	Not classified

Specific Target Organ Toxicity (STOT) – Single Exposure:

STOT SE Category 3: H336 – May cause drowsiness or dizziness by inhalation (narcotic effects). Central nervous system (CNS): may cause headache, dizziness, nausea, vomiting, confusion and, in severe cases, loss of consciousness.

Specific Target Organ Toxicity (STOT) – Repeated Exposure:

Low systemic toxicity is expected under repeated exposure conditions. Repeated exposure may cause skin dryness and cracking. No organ damage is expected from prolonged or repeated exposure.

11.2 Information on Other Hazards

Endocrine Disrupting Properties:

The product has no endocrine disrupting potential.

Other Hazards:

No other hazards known.



SAFETY DATA SHEET

In accordance with Regulation (EC) No 1907/2006

A-STAND 01 MIG JIMENEZ S.L.

English

Update date: 18/03/2026

Version: 1

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Name			Ecotoxicity
Type	Test	Species	Value
Fish	CL50	Pimephales promelas	6210 – 8120 mg/l Source: ECHA
Aquatic invertebrates	CE50	Daphnia magna	> 79 mg/l

12.2 Persistence and degradability

No data available.

12.3 Bioaccumulative potential

Significant bioaccumulation is not expected: (Log Pow = -0.24).

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product:

Recover or recycle where possible.

Contaminated packaging:

Disposal must be carried out in accordance with applicable regional, national and local laws and regulations.

14 TRANSPORT INFORMATION

14.1 UN number or ID number UN1090

14.2 UN proper shipping name ACETONE

14.3 Transport hazard class(es) 3
LABEL 3

14.4 Packing group II

14.5 Environmental hazards NO

14.6 Special precautions for user

Ensure that persons transporting the product know what to do in the event of an accident or spillage. Always transport in tightly closed containers, kept upright and secure. Ensure adequate ventilation.

Tunnel restriction code: D/E



SAFETY DATA SHEET		
In accordance with Regulation (EC) No 1907/2006		
A-STAND 01 MIG JIMENEZ S.L.		
English	Update date: 18/03/2026	Version: 1

Hazard identification number: 33

LIMITED QUANTITIES:

1 L inner packaging

EXCEPTED QUANTITIES:

E2 – 30 ml/g per inner packaging and 500 ml/g per outer packaging (max. 1000 packages per transport unit)

14.7 Maritime transport in bulk according to IMO instruments

Not relevant.

15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This Safety Data Sheet has been prepared in accordance with Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

This product is not subject to Regulation (EC) No. 1005/2009 of the European Parliament and of the Council on substances that deplete the ozone layer.

Regulation (EU) No. 649/2012 concerning the export and import of hazardous chemicals: not relevant.

Active substances included in Article 95 of Regulation (EU) No. 528/2012: not relevant.

SEVESO III

P5c – FLAMMABLE LIQUIDS

Threshold quantity (tonnes) for the application of requirements: 5,000 – 50,000 tonnes.

15.2 Chemical safety assessment

A Chemical Safety Assessment has not yet been carried out due to registration deadlines.

16 OTHER INFORMATION

This product must be stored, handled and used in accordance with good industrial hygiene practices.

This information reflects our current knowledge. It describes the product and should not be construed as a product specification.

The application of this information does not exempt the user from complying with current legislation.

The use of this information and the conditions of use of the product are the sole responsibility of the user.

Sources of information: Safety Data Sheets provided by our suppliers, to whose expertise and information we refer.